



**RAZER
INDUSTRIES PTY LTD**



Quality Endorsed Co.
AS9002 Lic.9386
Standards Australia

Product Information Sheet

Razer-Lag™ Natural Grade Pulley Lagging

Function

To provide positive drive through friction between the Lagging surface and the bottom cover of the belt.


- > To provide positive displacement of water and contaminants so as to maintain high friction values under all conditions.
- > To prevent wear to the metal pulley shell thus increasing pulley life expectancy.
- > To enable easy replacement without removing the pulley from the conveyor.

Advantages

- > Provided in 250mm wide strips with an 82mm-repeating pattern for cost-effective installation and pattern matching.
- > The unique block pattern ensures quieter operation and no section "Pull-out" under high torque conditions.
- > A special bonding layer of Neoprene rubber moulded to the back of the Razer-Lag enables higher lagging to pulley bond strength. This also means that abrasion resistance is not compromised to achieve high bond strength.
- > Superior water shedding performance from the Arrowhead Pattern.
- > Precision moulded and press cured ensures consistent dimensional and physical properties. Thickness is typically better than $\pm 0.25\text{mm}$.
- > Supplied pre buffed on edges and bonding face for ease of installation and T.I.R. accuracy.

Applications

- > On all pulley shells where shell life, water dispersion and/or material build up is a concern.
- > For substantially higher drive friction factors and increased service life in contaminated conditions please refer to our Ceramic Pulley Lagging Information.



Distributor Details:

PT. AUSTRALIAN BELT SCRAPER INDONESIA

Jalan Cihampelas 48B, Bandung 40116
West Java, Indonesia.

Phone +62 (22) 4264000

Fax +62 (22) 4232694

E-mail marketing@absindo.com

www.absindo.com

Razer Industries Pty Ltd

ABN 25 832 028 848

